Christopher Farr | cloth

Peacock Technical Sheet



Peacock Hot Pink Roman Blinds, Interior Design Tom Stringer

Composition100% Linen / 100% Solution Dyed PolyesterWidth52.8" / 134 CMPattern RepeatHorizontal Repeat 10.2" / 26CM Vertical Repeat 18.5" / 47CM (Half Drop)MartindaleLinen 20,000 Rubs / Polyester 40,000 RubsRoll LengthMax size 40M / 43 yard rolls (sold by linear metre / yard)WeightLinen 360 g/m2 Polyester 250 g/m2Minimum orderIM / 3 YardsLinen MaintenanceWeekly light vacuuming is desirable to remove dirt and dust particles and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more washable product.Linen FR RatingAll printed linens are supplied untreated and untested. Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner)PolyesterMachine washable at 30C. Do not twist or wring. Do not steam iron. Iron on reverse only.Polyester FireClass 1 anti-flame according to UNI 9176, B1 in Germany and M1 in France, NFPA 701-10, NFPA 260 and UFAC in Class 1.Commodity CodeLinen 5309III000 / Polyester 5512I9I0Country of OriginLinen UK / Polyester Italy		
Pattern Repeat Horizontal Repeat 10.2" / 26CM Vertical Repeat 18.5" / 47CM (Half Drop) Martindale Linen 20,000 Rubs / Polyester 40,000 Rubs Roll Length Max size 40M / 43 yard rolls (sold by linear metre / yard) Weight Linen 360 g/m2 Polyester 250 g/m2 Minimum order Linen Maintenance Weekly light vacuuming is desirable to remove dirt and dust particles and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more washable product. Linen FR Rating All printed linens are supplied untreated and untested. Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner) Polyester Machine washable at 30C. Do not twist or wring. Do not steam iron. Maintenance Polyester Fire Class I anti-flame according to UNI 9176, BI in Germany and MI in France, NFPA 70I-10, NFPA 260 and UFAC in Class I. Commodity Code Linen 5309III000 / Polyester 55I2I9I0	Composition	100% Linen / 100% Solution Dyed Polyester
MartindaleLinen 20,000 Rubs / Polyester 40,000 RubsRoll LengthMax size 40M / 43 yard rolls (sold by linear metre / yard)WeightLinen 360 g/m2 Polyester 250 g/m2Minimum orderIM / 3 YardsLinen MaintenanceWeekly light vacuuming is desirable to remove dirt and dust particles and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more washable product.Linen FR RatingAll printed linens are supplied untreated and untested. Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner)PolyesterMachine washable at 30C. Do not twist or wring. Do not steam iron. Iron on reverse only.Polyester FireClass 1 anti-flame according to UNI 9176, B1 in Germany and M1 in France, NFPA 701-10, NFPA 260 and UFAC in Class 1.Commodity CodeLinen 5309111000 / Polyester 55121910	Width	52.8" / 134 CM
Roll LengthMax size 40M / 43 yard rolls (sold by linear metre / yard)WeightLinen 360 g/m2 Polyester 250 g/m2Minimum orderIM / 3 YardsLinen MaintenanceWeekly light vacuuming is desirable to remove dirt and dust particles and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more washable product.Linen FR RatingAll printed linens are supplied untreated and untested. Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner)PolyesterMachine washable at 30C. Do not twist or wring. Do not steam iron. Iron on reverse only.Polyester FireClass 1 anti-flame according to UNI 9176, B1 in Germany and M1 in France, NFPA 701-10, NFPA 260 and UFAC in Class 1.Commodity CodeLinen 5309III000 / Polyester 5512I9I0	Pattern Repeat	Horizontal Repeat 10.2" / 26CM Vertical Repeat 18.5" / 47CM (Half Drop)
WeightLinen 360 g/m2 Polyester 250 g/m2Minimum orderIM / 3 YardsLinen MaintenanceWeekly light vacuuming is desirable to remove dirt and dust particles and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more washable product.Linen FR RatingAll printed linens are supplied untreated and untested. Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner)PolyesterMachine washable at 30C. Do not twist or wring. Do not steam iron. Iron on reverse only.Polyester FireClass 1 anti-flame according to UNI 9176, B1 in Germany and M1 in France, NFPA 701-10, NFPA 260 and UFAC in Class 1.Commodity CodeLinen 5309111000 / Polyester 55121910	Martindale	Linen 20,000 Rubs / Polyester 40,000 Rubs
Minimum orderIM / 3 YardsLinen MaintenanceWeekly light vacuuming is desirable to remove dirt and dust particles and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more washable product.Linen FR RatingAll printed linens are supplied untreated and untested. Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner)PolyesterMachine washable at 30C. Do not twist or wring. Do not steam iron. Iron on reverse only.Polyester FireClass 1 anti-flame according to UNI 9176, B1 in Germany and M1 in France, NFPA 701-10, NFPA 260 and UFAC in Class 1.Commodity CodeLinen 5309111000 / Polyester 55121910	Roll Length	Max size 40M / 43 yard rolls (sold by linear metre / yard)
Linen Maintenance Weekly light vacuuming is desirable to remove dirt and dust particles and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more washable product. Linen FR Rating All printed linens are supplied untreated and untested. Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner) Polyester Maintenance Polyester Fire Class I anti-flame according to UNI 9176, BI in Germany and MI in France, NFPA 701-10, NFPA 260 and UFAC in Class I. Linen 5309111000 / Polyester 55121910	Weight	Linen 360 g/m2 Polyester 250 g/m2
and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more washable product. Linen FR Rating All printed linens are supplied untreated and untested. Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner) Polyester Machine washable at 30C. Do not twist or wring. Do not steam iron. Iron on reverse only. Polyester Fire Rating Class I anti-flame according to UNI 9176, BI in Germany and MI in France, NFPA 701-10, NFPA 260 and UFAC in Class I. Linen 5309111000 / Polyester 55121910	Minimum order	1M / 3 Yards
Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when covered with a barrier cloth (schedule 3 interliner) Polyester Machine washable at 30C. Do not twist or wring. Do not steam iron. Iron on reverse only. Polyester Fire Class 1 anti-flame according to UNI 9176, B1 in Germany and M1 in France, NFPA 701-10, NFPA 260 and UFAC in Class 1. Commodity Code Linen 5309111000 / Polyester 55121910	Linen Maintenance	and greatly extends the life of the fabric. Most of our prints have good resistance to being dry-cleaned in Perchloroethylene, but a spot test is recommended to ascertain temperature and purity values beforehand. Custom print on performance polyester for a more
MaintenanceIron on reverse only.Polyester FireClass 1 anti-flame according to UNI 9176, B1 in Germany and M1 inRatingFrance, NFPA 701-10, NFPA 260 and UFAC in Class 1.Commodity CodeLinen 5309111000 / Polyester 55121910	Linen FR Rating	Fabrics made of at least 75% natural fibres can be Cigarette tested upon request to comply with Domestic Upholstery regulations when
Polyester Fire Class 1 anti-flame according to UNI 9176, B1 in Germany and M1 in France, NFPA 701-10, NFPA 260 and UFAC in Class 1. Commodity Code Linen 5309111000 / Polyester 55121910	Polyester	Machine washable at 30C. Do not twist or wring. Do not steam iron.
Rating France, NFPA 701-10, NFPA 260 and UFAC in Class 1. Commodity Code Linen 5309111000 / Polyester 55121910	Maintenance	Iron on reverse only.
Commodity Code Linen 5309111000 / Polyester 55121910	Polyester Fire	Class I anti-flame according to UNI 9176, BI in Germany and MI in
·	Rating	France, NFPA 701-10, NFPA 260 and UFAC in Class 1.
Country of Origin Linen UK / Polyester Italy	Commodity Code	Linen 5309111000 / Polyester 55121910
	Country of Origin	Linen UK / Polyester Italy

Inquire for custom projects No minimum order on standard wallpaper, vinyl, linen, cotton or Trevira. **Custom lead time** 2-3 weeks sampling, 4-8 weeks production from receipt of 50% deposit. **Inquire for contract projects** 40 Metre minimums for Performance Polyester FR, 100 Metre minimums for ASTM Vinyl.

Contract lead time 6-8 weeks sampling, 8-10 weeks production from receipt of 50% deposit and confirmed order.

Christopher Farr | cloth

Peacock Technical Sheet

Custom Submittal Form

We thrive on creative conversations and love to be challenged, this combined with our intimate knowledge of colour, printing and weaving allows us to tackle almost any customisation project. With simple instruction on colour we can adapt the palette of a design to match any interior scheme.

Colours

We can easily alter the colours of our prints to adapt them for a particular scheme. We require guidance on colour from any source, such as fabric cutting, pantone or paint swatch references.

Base Qualities

We can alter the composition of our fabrics to make them more suitable for a given use. Whether we are printing onto a more durable ground for upholstery, Trevira or vinyl for flame retardancy, polyester for outdoor use, we apply the same care and attention.



Ground Options (please tick box that applies)

Peacock Design

THIS FORM MUST BE SUBMITTED WITH HARD COLOUR REFERENCES TO YOUR SHOWROOM WHO WILL PROVIDE A FORMAL QUOTE BASED ON INFORMATION PROVIDED.

(C	0	/	9	u	r	i	1																																	
 -	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	

Ground Colour
Print to standard O
Client to submit
Design Notes (scale change / motif adjustments)
Quantity Required

Non-Woven Wallpaper (White or Ivory)	Raffia Wallpaper (50 M/YD Minimums apply)
Vinyl Wallpaper (Flat or Linen	Cotton (several options available)
Emboss)	
Trevira Polyester FR (several options	Outdoor Performance Polyester FR
available)	(40 M/YD Minimums apply)
Light Linen (Ecru or Natural)	Other - please specify:
Heavy Linen (Ecru or Natural)	

Custom print on contract vinyl to meet EN 13501 B-s2, d0 + ASTM E84 Class A standards. Custom print on Performance Polyester FR to meet class 1 anti-flame according to UNI 9176, B1 in Germany and M1 in France, NFPA 701-10, NFPA 260 and UFAC in Class 1.