

Abaca Technical Sheet



Abaca Sky Wallpaper

| | |
|------------------------------|--|
| Composition | 100% Abaca on Non-woven |
| Width | 33.5" /85CM |
| Roll Length | 8M / 8.7 Yard rolls (sold by the roll) |
| Weight | Abaca 325 g/m2 |
| Wallpaper Maintenance | We do not recommend cleaning our delicate hand printed wallpapers but if necessary, please wipe the area gently with a non-abrasive cloth to remove dirt. Brush raffia wallpaper with dry brittle brush to remove dirt. Custom print on vinyl for a more washable product. |
| Fire Rating | EN 13501-1:2002 Class B, s1, d0, ASTM E84-19 Class A |
| Commodity Code | 48021000 |
| Country of Origin | China |

IMPORTANT HANGING INFORMATION

Before you start please ensure the following:

- The wallcoverings are as ordered - as specified, as labelled (identification samples available immediately)
- You have sufficient material to complete the job in the same batch
- Batch numbers are identical - never mix batches on the wall, never in fill with off-cuts
- The correct adhesive for your individual site circumstances
- Adequate site conditions – good lighting for correct inspection, minimum ambient temperature of 10°C. Good ventilation & clean working conditions.
- Avoid excessive ambient temperatures – radiators should ideally be removed before and for the 24 hours after hanging. If this is not possible, they must be turned off and kept off until the wallcovering has fully dried.
- Please trial hang a wallpaper sample 24 hours prior to full hang.

N.B Joints on some designs such as woven textiles, grass cloths and other horizontal patterns will be visible and may give a panelled effect.

Please ensure you carry out a trial hang on a sample of paper 24 hours prior to hanging your full order. No claims will be accepted for hanging charges or for consequential loss. Continue inspection throughout hanging process, inspecting each drop as you hang it. Never assume shading will dry out.

SURFACE PREPARATION

Correct identification of surfaces, and the appropriate preparation is critical to successful hanging. All surfaces should be:

- **Clean** – Remove all surface contamination, e.g dirt, grease and pigmented marks, eg felt pen etc. Wash off using a detergent solution, rinse and allow to dry thoroughly.
- **Sound & Even** – Free of flaking paint, old wallpaper/backing. Evidence of previous adhesive should be removed with hot water. Weak skims/ surfaces and uneven surfaces will require remedial action.
- **Uniform in Colour** – To prevent show through equalise colour.
- **Dry in Depth** – Tested with good moisture meter.
- **Keyed** – With coarse, dry sandpaper.
- **Lining Paper** – We recommend the use of lining paper.

HANGING THE WALLCOVERINGS

| PRODUCT | RECOMMENDED ADHESIVES | APPLY ADHESIVE TO | DIRECTION OF DROPS | METHOD OF JOINT |
|------------------------------|--|---|---------------------|-----------------|
| Abaca on Non-woven wallpaper | Good quality heavy weight ready mix adhesive such as Beeline Heavy Grade | Paste the Wall (We recommend the use of lining paper) | As directed on roll | Butt Join |

This information is supplied in good faith, but without guarantee and on the understanding that the installer will have decorating knowledge to work with differing site or atmospheric conditions. A sample hang must be carried out 24 hours prior to full hang.