

*Sea Collage Vinyl Technical Sheet*



*Sea Collage Stone Vinyl, designed by Sandra Blow*

<b>Composition</b>	Non-woven backed Vinyl Wallpaper FSC Certified
<b>Width</b>	47.2" / 120 CM
<b>Pattern Repeat</b>	Vertical Repeat 62.2" / 158 CM
<b>Roll Length</b>	8M / 8.7 YDS (Untrimmed) Max size for custom production 15M / 16 YD Rolls
<b>Weight</b>	300 g/m <sup>2</sup>
<b>Minimum order</b>	1 Roll (8M / 8.7 YDS)
<b>Maintenance</b>	Vinyl is washable with mild detergent and a non-abrasive cloth. Vinyl has very good stain and knock resistance.
<b>Hanging Method</b>	Paste the wall. Use a quality pre-mix tub adhesive for non-woven wallpapers. Avoid contact with the printed surface.
<b>UK FR Rating</b>	EN BS 13501-1:2007+A1:2009 Class O, s1, d0
<b>USA FR Rating</b>	ASTM E 84-12c Class A
<b>Commodity Code</b>	48021000
<b>Country of Origin</b>	UK
<b>Custom</b>	Any custom colour or design. 1 roll minimum.

Sea Collage Vinyl Technical Sheet

Custom Submittal Form

We thrive on creative conversations and love to be challenged, this combined with our intimate knowledge of colour, printing and weaving allows us to tackle almost any customisation project. With simple instruction on colour we can adapt the palette of a design to match any interior scheme.

Colours

We can easily alter the colours of our prints to adapt them for a particular scheme. We require guidance on colour from any source, such as fabric cutting, pantone or paint swatch references.

Base Qualities

We can alter the composition of our fabrics to make them more suitable for a given use. Whether we are printing onto a more durable ground for upholstery, Trevira or vinyl for flame retardancy, polyester for outdoor use, we apply the same care and attention.



Sea Collage

THIS FORM MUST BE COMPLETED AND SUBMITTED TO YOUR SHOWROOM WHO WILL PROVIDE A FORMAL QUOTE BASED ON INFORMATION PROVIDED.

Ground Colour (White)

Print to standard

Client to submit

Pattern Colours

Colour 1 -----

Colour 2 -----

Design Notes (scale change / motif adjustments)

Quantity Required

Ground Options (please tick box that applies)

<input type="checkbox"/>	Non-Woven Wallpaper (White or Ivory)	Raffia Wallpaper (50 M/YD Minimums apply)
<input type="checkbox"/>	Vinyl Wallpaper (Flat or Linen Emboss)	Cotton (several options available)
<input type="checkbox"/>	Trevira Polyester FR (several options available)	Outdoor Performance Polyester FR (40 M/YD Minimums apply)
<input type="checkbox"/>	Light Linen (Ecrú or Natural)	Other - please specify:
<input type="checkbox"/>	Heavy Linen (Ecrú or Natural)	

*Sea Collage Vinyl Technical Sheet*

**IMPORTANT HANGING INFORMATION**

Before you start please ensure the following:

- The wallcoverings are as ordered - as specified, as labelled (identification samples available immediately)
- You have sufficient material to complete the job in the same batch
- Batch numbers are identical - never mix batches on the wall, never in fill with off-cuts
- The correct adhesive for your individual site circumstances
- Adequate site conditions – good lighting for correct inspection, minimum ambient temperature of 10°C. Good ventilation & clean working conditions.
- Avoid excessive ambient temperatures – radiators should ideally be removed before and for the 24 hours after hanging. If this is not possible, they must be turned off and kept off until the wallcovering has fully dried.
- Please trial hang a wallpaper sample 24 hours prior to full hang.

N.B Joints on some designs such as woven textiles, grass cloths and other horizontal patterns will be visible and may give a panelled effect.

Please ensure you carry out a trial hang on a sample of paper 24 hours prior to hanging your full order.

No claims will be accepted for hanging charges or for consequential loss. Continue inspection throughout hanging process, inspecting each drop as you hang it. Never assume shading will dry out.

**SURFACE PREPARATION**

Correct identification of surfaces, and the appropriate preparation is critical to successful hanging. All surfaces should be:

- **Clean** – Remove all surface contamination, e.g dirt, grease and pigmented marks, eg felt pen etc. Wash off using a detergent solution, rinse and allow to dry thoroughly.
- **Sound & Even** – Free of flaking paint, old wallpaper/backing. Evidence of previous adhesive should be removed with hot water. Weak skims/ surfaces and uneven surfaces will require remedial action.
- **Uniform in Colour** – To prevent show through equalise colour.
- **Dry in Depth** – Tested with good moisture meter.
- **Keyed** – With coarse, dry sandpaper.
- **Lining Paper** – We recommend the use of lining paper.

**HANGING THE WALLCOVERINGS**

PRODUCT	RECOMMENDED ADHESIVES	APPLY ADHESIVE TO	DIRECTION OF DROPS	METHOD OF JOINT
Sea Collage Vinyl Wallpaper	Good quality heavy weight ready mix adhesive such as Beeline Heavy Grade	Paste the Wall	As directed on roll	Overlap and splice

This information is supplied in good faith, but without guarantee and on the understanding that the installer will have decorating knowledge to work with differing site or atmospheric conditions. A sample hang must be carried out 24 hours prior to full hang.